


10 TON SOLAR ROAD MARKERS



Features

Solar Road Markers or lane markers are a low-cost, self-contained, rechargeable, LED illuminated marker. Visible up to 800 metres they are used to reduce speed or signal driver attention to common features, hazards and dangerous bends on our roads. Commonly used on sharp corners, pedestrian refuges, traffic islands and dividing lines. The aluminium casings are rated to 10 tons, single or dual sided in static or flashing modes providing clear and visible traffic guidance in all weather conditions. Multiple colour options are available. These units require no maintenance and generate no ongoing operational costs.



Luminaire Height	23mm
Lumen Output	48 lm
LED Output	0.2W

Trafficable, self-contained, rechargeable

Visible over 800 metres

Single or dual sided

Static or flashing modes

Easy to install

10 Ton load rating

> 5 year expected lifespan

Cast aluminium and polycarbonate construction

IP67 waterproof rating

Zero maintenance or ongoing costs

Various colour options available

Automatic dusk to dawn lighting

2 year warranty for faulty workmanship or component failure not influenced by external mean



+86- 13733560139



www.ecosolarlights.com



sales@ecosolarlights.com

10 TON SOLAR ROAD MARKER SPECIFICATION



Applications

Roadways | Car parks | Cycleways | Curb marking

Technical Data

Solar Panel Wattage	0.3W
LED Output	0.2W
Lumen Output	48 lm
Battery Type	Nickel–metal hydride
Battery Specifications	0.6AH 1.2V (0.72 Wh)
Autonomy	> 5 nights
Correlated Colour Temp (CCT)	6000K
Fixture Size	105mm x 105mm x 23mm
Light Source	Epistar F5 LED
Recharge	5 hours
Mounting Height	23mm
Mounting	Surface mount, no spigot
Finish	Aluminum/polycarbonate
Warranty Period	2 years
SKU	SORM10

Mode of Operation

Automatic dusk to dawn lighting. Flashing or static.
Multiple colours options available.

As we continue to improve the products function and/or design specifications and data provided may change without notice. Errors and omissions accepted.