

# UFO V2 SOLAR LIGHT SPECIFICATION



## Features

The UFO style of all-in-one solar lighting is designed to be aesthetically pleasing while offering a functional 360° lighting pattern. The premium 3030 LED's provide exceptional light output distributed over a wide area.

The UFO lights unique shape, black coated cast aluminium body adds to the style and provides a corrosion resistant finish suitable for installation in coastal environments. Constant all night lighting, P.I.R (passive infrared sensor) operated or a combination of both are easily programmed by remote control. Designed for use in parks, gardens, courtyards, playgrounds or decks.



|                  |           |
|------------------|-----------|
| Luminaire Height | 2.5 - 4m  |
| Lumen Output     | 2350 lm   |
| LED Output       | 15W (max) |

Stylish and functional solar lighting

360° lighting pattern for illuminating larger areas

Ideal for illuminating courtyards, decks & park areas

Smart Lighting Program

Commercial grade solar lighting

157 lumen per watt output

Corrosion resistant aluminium body with premium finish

Premium LifePO4 battery

Custom powder coated poles manufactured on request

Simple plug and play installation

2 year warranty for faulty workmanship or component failure not influenced by external means

# UFO V2 SOLAR LIGHT SPECIFICATION



## Applications

Courtyard | Plaza | 360° lighting | Decks

## Technical Data

|                              |                                |
|------------------------------|--------------------------------|
| Solar Panel Wattage          | 32W                            |
| LED Output                   | 15W                            |
| Lumen Output                 | 2350 lm (max)                  |
| Battery Type                 | LifePO4                        |
| Battery Specifications       | 45AH 3.2V (144Wh)              |
| Correlated Colour Temp (CCT) | 5000K                          |
| Fixture Size                 | 560 (l) x 560 (w) x 230 (h) mm |
| Light Source                 | 3030 SMD                       |
| Recharge                     | 5 hours                        |
| Mounting Height              | 2.5 - 4 metres                 |
| Mounting                     | 76-90mm column - 76mm spigot   |
| Finish                       | Powder-coated cast aluminium   |
| Warranty Period              | 2 years                        |
| SKU                          | SOLL0 20/V2                    |

## Mode of Operation

Auto On at dusk, 100% output for 3 hours, 70% output for 5 hours, 40% output for 4 hours, Auto Off

As we continue to improve the products function and/or design specifications and data provided may change without notice. Errors and omissions accepted.